

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 03-065659

(43)Date of publication of application : 20.03.1991

(51)Int.Cl.

G01R 1/073
G01R 31/26
H01L 21/66

(21)Application number : 01-202081

(71)Applicant : TAKEDA SANGYO KK

(22)Date of filing : 02.08.1989

(72)Inventor : BANDO KENJIRO


(54) PROBE CARD

(57)Abstract:

PURPOSE: To reduce the contact pressure of a wafer chip to a pad thereby preventing the pad from being damaged by providing, in place of a contact needle, a bump having a circuit printed on a transparent plate.

CONSTITUTION: Bumps 4, 4 are pressed in contact with a pad of a wafer chip from above. At this time, the grounding state is monitored through a transparent plate 3 from a central hole 1 of a card substrate 2. If the pad and bumps 4, 4 are not in uniform contact with each other, they are adjusted by parallel adjusting screws 7, 7.

After the pad and bumps 4, 4 are adjusted in uniform contact visually, a high frequency wave is applied to a vibrating plate 8, causing vibration of the plate. Then, electric characteristic test is conducted. The vibration of the plate 8 is transmitted to the transparent plate 3 itself, and the bumps 4, 4 are eventually vibrated. Since an oxide film formed on the pad is slightly delaminated by the vibration of the bumps 4, 4, conductive property is enhanced, enabling favorable electric characteristic test.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

BEST AVAILABLE COPY

[Kind of final disposal of application other than
the examiner's decision of rejection or
application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office